


Piedmont

FRP CARTRIDGE FILTER HOUSING



FRP CARTRIDGE FILTER HOUSING

(FIBERGLASS REINFORCED POLYESTER)

Available in different capacities, our filter housings are made of fiberglass reinforced polyester (FRP) and include unique components and design elements making them fit for multiple brands of universal cartridge elements. A cost-effective solution, our filter housings are a reliable protection for your BWRO and SWRO membrane systems.

Piedmont's cartridge filter housings are meant for new and existing water treatment plants.



OUR STANDARD FILTER HOUSINGS ARE DESIGNED WITH GROOVED CONNECTIONS. FLANGE OPTION AVAILABLE.

Features / Benefits

- Designed to ASME-X/EN13121 / Ad Merkblatt / BS 4994/ AS1210 code
- Design temperatures up to 90 °C / 194 °F
- Design pressure up to 10 bar / 150 psi
- Horizontal and vertical configuration available
- Internal lining of vinyl ester Derakane 411, FDA/NSF compliant
- Davit arm and swing bolts available
- Coupling or flanged connection available



CARTRIDGES

(& CONNECTIONS)



Reinforced, state of the art internal cartridge support rods made out of FRP and polyamide material with a knife-edged sealing for Double Open End (DOE) cartridge connection.

Suitable for both string wound and melt-blown cartridges

Outside to inside flow

Internal support rods

- Larger open flow area resulting in lower pressure drop
- High-speed assembly nut for easy and fast cartridge replacement
- Anti-rotation notch ensuring complete rod will not rotate when removing upper nut
- Careful selection of materials allowing for design temperatures of 90°C
- Increased mechanical resistance by improved manufacturing process
- Absence of glue
- Attractive design



Lower DOE
knife-edged
cartridge seat



Upper DOE
knife-edged
high speed nut





SOE connections available

Spring type connection also available


INTERNAL & EXTERNAL FEATURES





MATERIALS LISTING

1. FRP rod
2. Plastic over injection parts in PA + 30% FRP
3. Commercial PA + 30% FRP white nut
4. EPDM gaskets for support rod sealing
5. 2 x commercial PA + 30% FRP black nut
6. Deflector plate (FRP)
7. PVC/PP material Internal guide plate
8. FRP Housing
 - Vinyl Ester resin chemical barrier (FDA & NSF compliant)
 - Isophthalic resin structural layer
9. EPDM gaskets for main flanges
10. Support legs can be in:
 - FRP
 - Carbon steel painted - ISO 12944 C5M (areas with high salinity)
 - Stainless steel (A4 or A2)
11. Inlet/outlet grooved connection (Flange available)
12. Hoist (lifting arm) - Stainless steel *on larger models only*
13. Stainless steel bolts (A4 or A2), nuts and washers - X-Style only



Q

7

QH

9

XS

11

XSH

13

XB

15

HVQX

17

HHQX



19

BQX

21

SQX

23




Q-STYLE SPECIFICATIONS

TECHNICAL DATA SHEET



OUR STANDARD FILTER HOUSINGS ARE DESIGNED WITH PIEDMONT COUPLINGS (OR SIMILAR) FOR A MORE ECONOMIC AND SIMPLE CONNECTION TO YOUR PIPING. HOIST (LIFTING ARM) OPTIONAL.




MATERIALS

- 1. Shell & cap / Main body: FRP
- 3. Support legs: SS 316
- 4. Inlet flange: FRP
- 5. Outlet flange: FRP
- 6. Air vent: FRP / PP
- 7. Clean drain: FRP / PP
- 8. Deflector plate: FRP
- 9. Tube sheet: PVC / FRP
- 10. Guide plate: PVC / PP
- 11. Lifting lugs: FRP
- 13. Main body gaskets: EPDM
- 15. Support rod: PA + FRP
- 16. Cartridge element: PP
- 17. Dirty drain: FRP
- 18. O-ring support plate: PVC
- 19. Structural plate: FRP
- 20. Securing plate: PP
- 21. Locking rings: PP

CHARACTERISTICS

Flow rates: 6 - 550 m³/h
N° elements: 3 - 70
Elements length: 30/40/50/70
Cartridge flow: Outside - Inside
Housing layout: Vertical
Features: Quick opening, no bolts
Ideal: Modular / skid / container
Design pressure: 6/10 bar




Q-STYLE Quick Opening Cartridge Filter Housing

Filter Housing model reference	Cartridges	Flow at 3gpm - 0,68 m ³ /h per 10"	Flow at 4gpm - 0,91 m ³ /h per 10"	Flow at 5gpm - 1,12 m ³ /h per 10"	N1 / N2 (inch / mm)	A (inch / mm)	B (inch / mm)	C (inch / mm)	D (inch / mm)	E (inch / mm)
	Qty. x Length									
Q-PCF-3-30	3 x 30	27 / 6	36 / 8	45 / 10	2 / 50	39 / 997	4 / 104	6 / 150	42 / 1074	6 / 155
Q-PCF-3-40	3 x 40	36 / 8	48 / 11	60 / 13	2 / 50	49 / 1251	4 / 104	6 / 150	52 / 1328	6 / 155
Q-PCF-3-50	3 x 50	45 / 10	60 / 14	75 / 17	2 / 50	59 / 1505	4 / 104	6 / 150	62 / 1582	6 / 155
Q-PCF-5-30	5 x 30	45 / 10	60 / 14	75 / 17	2 / 50	39 / 997	4 / 104	8 / 200	42 / 1074	7 / 180
Q-PCF-5-40	5 x 40	60 / 14	80 / 18	100 / 22	2 / 50	49 / 1251	4 / 104	8 / 200	52 / 1328	7 / 180
Q-PCF-5-50	5 x 50	75 / 17	100 / 23	125 / 28	2 / 50	59 / 1505	4 / 104	8 / 200	62 / 1582	7 / 180
Q-PCF-6-30	6 x 30	54 / 12	72 / 16	90 / 20	2 / 50	20 / 518	10 / 250	10 / 250	61 / 1559	8 / 210
Q-PCF-6-40	6 x 40	72 / 16	96 / 22	120 / 27	2 / 50	20 / 518	10 / 250	10 / 250	71 / 1813	8 / 210
Q-PCF-6-50	6 x 50	90 / 20	120 / 27	150 / 34	3 / 80	20 / 518	10 / 250	10 / 250	81 / 2067	9 / 235
Q-PCF-12-30	12 x 30	108 / 24	144 / 33	180 / 40	3 / 80	24 / 618	11 / 289	12 / 300	61 / 1559	10 / 260
Q-PCF-12-40	12 x 40	144 / 33	192 / 44	240 / 54	3 / 80	24 / 618	11 / 289	12 / 300	71 / 1813	10 / 260
Q-PCF-12-50	12 x 50	180 / 41	240 / 55	300 / 67	4 / 100	24 / 618	11 / 289	12 / 300	81 / 2067	10 / 260
Q-PCF-22-30	22 x 30	198 / 45	264 / 60	330 / 74	4 / 100	20 / 497	10 / 254	16 / 400	61 / 1559	12 / 310
Q-PCF-22-40	22 x 40	264 / 60	352 / 80	440 / 99	4 / 100	20 / 497	10 / 254	16 / 400	71 / 1813	12 / 310
Q-PCF-22-50	22 x 50	330 / 75	440 / 100	550 / 123	6 / 150	23 / 583	10 / 254	16 / 400	81 / 2067	12 / 310
Q-PCF-35-30	35 x 30	315 / 71	420 / 96	525 / 118	6 / 150	21 / 533	10 / 255	20 / 500	61 / 1559	14 / 360
Q-PCF-35-40	35 x 40	420 / 95	560 / 127	700 / 157	6 / 150	21 / 533	10 / 255	20 / 500	71 / 1813	14 / 360
Q-PCF-35-50	35 x 50	525 / 119	700 / 159	875 / 196	6 / 150	21 / 533	10 / 255	20 / 500	81 / 2067	14 / 360
Q-PCF-50-30	50 x 30	450 / 102	600 / 137	750 / 168	6 / 150	25 / 628	12 / 299	24 / 600	66 / 1679	16 / 410
Q-PCF-50-40	50 x 40	600 / 136	800 / 182	1000 / 224	6 / 150	25 / 628	12 / 299	24 / 600	76 / 1933	16 / 410
Q-PCF-50-50	50 x 50	750 / 170	1000 / 228	1250 / 280	8 / 200	25 / 628	11 / 292	24 / 600	86 / 2187	16 / 410
Q-PCF-70-30	70 x 30	630 / 143	840 / 191	1050 / 235	8 / 200	27 / 678	14 / 350	28 / 700	70 / 1769	20 / 500
Q-PCF-70-40	70 x 40	840 / 190	1120 / 255	1400 / 314	8 / 200	27 / 678	14 / 350	28 / 700	80 / 2023	20 / 500
Q-PCF-70-50	70 x 50	1050 / 238	1400 / 319	1750 / 392	8 / 200	27 / 678	14 / 350	28 / 700	90 / 2277	20 / 500
Q-PCF-70-70	70 x 70	1470 / 333	1960 / 446	2450 / 549	10 / 250	27 / 698	13 / 325	28 / 700	110 / 2785	20 / 500

QH-STYLE SPECIFICATIONS

TECHNICAL DATA SHEET



OUR STANDARD FILTER HOUSINGS ARE DESIGNED WITH PIEDMONT COUPLINGS (OR SIMILAR) FOR A MORE ECONOMIC AND SIMPLE CONNECTION TO YOUR PIPING. HOIST (LIFTING ARM) OPTIONAL.

MATERIALS



- 1. Shell & cap / Main body: FRP
- 3. Support legs: SS 316
- 4. Inlet flange: FRP
- 5. Outlet flange: FRP
- 6. Air vent: FRP / PP
- 7. Clean drain: FRP / PP
- 8. Deflector plate: FRP
- 9. Tube sheet: PVC / FRP
- 10. Guide plate: PVC / PP

- 11. Lifting lugs: FRP
- 14. Main body gaskets: EPDM
- 15. Support rod: PA + FRP
- 16. Cartridge element: PP
- 17. Dirty drain: FRP
- 18. O-ring support plate: PVC
- 19. Structural plate: FRP
- 20. Securing plate: PP
- 21. Locking rings: PP



CHARACTERISTICS

Flow rates: 6 - 550 m³/h
N° elements: 3 - 70
Elements length: 30/40/50/70
Cartridge flow: Outside - Inside
Housing layout: Horizontal
Features: Quick opening, no bolts
Ideal: Modular / skid / container
Design pressure: 6/10 bar





QH-STYLE Quick Opening Cartridge Filter Housing

Filter Housing model reference	Cartridges	Flow at 3gpm - 0,68 m ³ /h per 10"	Flow at 4gpm - 0,91 m ³ /h per 10"	Flow at 5gpm - 1,12 m ³ /h per 10"	N1 / N2 (inch / mm)	A (inch / mm)	B (inch / mm)	C (inch / mm)	D (inch / mm)	E (inch / mm)	F (inch / mm)
	Qty. x Length										
QH-PCF-3-30	3 x 30	27 / 6	36 / 8	45 / 10	2 / 40	39 / 997	4 / 104	6 / 150	42 / 1074	6 / 155	8 / 215
QH-PCF-3-40	3 x 40	36 / 8	48 / 11	60 / 13	2 / 40	49 / 1251	4 / 104	6 / 150	52 / 1328	6 / 155	8 / 215
QH-PCF-3-50	3 x 50	45 / 10	60 / 14	75 / 17	2 / 50	59 / 1505	4 / 104	6 / 150	62 / 1582	6 / 155	8 / 215
QH-PCF-5-30	5 x 30	45 / 10	60 / 14	75 / 17	2 / 50	39 / 997	4 / 104	8 / 200	42 / 1074	7 / 180	9 / 240
QH-PCF-5-40	5 x 40	60 / 14	80 / 18	100 / 22	2 / 80	49 / 1251	4 / 104	8 / 200	52 / 1328	7 / 180	9 / 240
QH-PCF-5-50	5 x 50	75 / 17	100 / 23	125 / 28	2 / 80	59 / 1505	4 / 104	8 / 200	62 / 1582	7 / 180	9 / 240
QH-PCF-6-30	6 x 30	54 / 12	72 / 16	90 / 20	2 / 50	20 / 518	10 / 250	10 / 250	61 / 1559	8 / 210	10 / 265
QH-PCF-6-40	6 x 40	72 / 16	96 / 22	120 / 27	2 / 80	20 / 518	10 / 250	10 / 250	71 / 1813	8 / 210	10 / 265
QH-PCF-6-50	6 x 50	90 / 20	120 / 27	150 / 34	3 / 80	20 / 518	10 / 250	10 / 250	81 / 2067	9 / 235	10 / 265
QH-PCF-12-30	12 x 30	108 / 24	144 / 33	180 / 40	3 / 80	24 / 618	11 / 289	12 / 300	61 / 1559	10 / 260	11 / 290
QH-PCF-12-40	12 x 40	144 / 33	192 / 44	240 / 54	3 / 80	24 / 618	11 / 289	12 / 300	71 / 1813	10 / 260	11 / 290
QH-PCF-12-50	12 x 50	180 / 41	240 / 55	300 / 67	4 / 100	24 / 618	11 / 289	12 / 300	81 / 2067	10 / 260	11 / 290
QH-PCF-22-30	22 x 30	198 / 45	264 / 60	330 / 74	4 / 100	20 / 497	10 / 254	16 / 400	61 / 1559	12 / 310	13 / 340
QH-PCF-22-40	22 x 40	264 / 60	352 / 80	440 / 99	4 / 125	20 / 497	10 / 254	16 / 400	71 / 1813	12 / 310	13 / 340
QH-PCF-22-50	22 x 50	330 / 75	440 / 100	550 / 123	6 / 125	23 / 583	10 / 254	16 / 400	81 / 2067	12 / 310	13 / 340
QH-PCF-35-30	35 x 30	315 / 71	420 / 96	525 / 118	6 / 125	21 / 533	10 / 255	20 / 500	61 / 1559	14 / 360	15 / 390
QH-PCF-35-40	35 x 40	420 / 95	560 / 127	700 / 157	6 / 150	21 / 533	10 / 255	20 / 500	71 / 1813	14 / 360	15 / 390
QH-PCF-35-50	35 x 50	525 / 119	700 / 159	875 / 196	6 / 200	21 / 533	10 / 255	20 / 500	81 / 2067	14 / 360	15 / 390
QH-PCF-50-30	50 x 30	450 / 102	600 / 137	750 / 168	6 / 150	25 / 628	12 / 299	24 / 600	66 / 1679	16 / 410	17 / 440
QH-PCF-50-40	50 x 40	600 / 136	800 / 182	1000 / 224	6 / 200	25 / 628	12 / 299	24 / 600	76 / 1933	16 / 410	17 / 440
QH-PCF-50-50	50 x 50	750 / 170	1000 / 228	1250 / 280	8 / 200	25 / 628	11 / 292	24 / 600	86 / 2187	16 / 410	17 / 440
QH-PCF-70-30	70 x 30	630 / 143	840 / 191	1050 / 235	8 / 200	27 / 678	14 / 350	28 / 700	70 / 1769	20 / 500	19 / 490
QH-PCF-70-40	70 x 40	840 / 190	1120 / 255	1400 / 314	8 / 200	27 / 678	14 / 350	28 / 700	80 / 2023	20 / 500	19 / 490
QH-PCF-70-50	70 x 50	1050 / 238	1400 / 319	1750 / 392	8 / 250	27 / 678	14 / 350	28 / 700	90 / 2277	20 / 500	19 / 490
QH-PCF-70-70	70 x 70	1470 / 333	1960 / 446	2450 / 549	10 / 300	27 / 698	13 / 325	28 / 700	110 / 2785	20 / 500	18 / 450

XS-STYLE SPECIFICATIONS

TECHNICAL DATA SHEET




MATERIALS

1. Shell & cap / Main body: FRP
2. Closure cover plate: FRP
3. Support legs: FRP
4. Inlet flange: FRP
5. Outlet flange: FRP
6. Air vent: FRP
7. Clean drain: FRP
8. Deflector plate: FRP
9. Tube sheet: PVC / FRP
10. Guide plate: PVC / PP
11. Lifting lugs: FRP
12. Closure bolts: SS 316
13. Main body gaskets: EPDM
14. Hoist (lifting arm): SS 316
15. Support rod: PA + FRP
16. Cartridge element: PP
22. Internal support rod: FRP + PA

CHARACTERISTICS

Flow rates: 245 - 3200 m³/h
N° elements: 90 - 410
Elements length: 30/40/50/70
Cartridge flow: Outside - Inside
Housing layout: Vertical
Features: Side inlet / bottom outlet
 davit arm available
Optional: Swing bolts
Ideal: High flows and stand alone
Design pressure: 6/10 bar




XS-STYLE

Side Inlet type Higher Flow Cartridge Filter Housing

Filter Housing model reference	Cartridges	Flow at 3gpm - 0,68 m³/h per 10"	Flow at 4gpm - 0,91 m³/h per 10"	Flow at 5gpm - 1,12 m³/h per 10"	N1 / N2 (inch / mm)	A (inch / mm)	B (inch / mm)	C (inch / mm)	D (inch / mm)	E (inch / mm)
	Qty. x Length									
XS-PCF-90-40	90 x 40	1080 / 245	1440 / 328	1800 / 403	10 / 250	72 / 1822	27 / 685	31 / 800	110 / 2791	25 / 640
XS-PCF-90-50	90 x 50	1350 / 306	1800 / 410	2250 / 504	10 / 250	82 / 2076	27 / 685	31 / 800	120 / 3045	25 / 640
XS-PCF-118-40	118 x 40	1416 / 321	1888 / 430	2360 / 529	10 / 250	73 / 1843	27 / 685	35 / 900	115 / 2911	28 / 700
XS-PCF-118-50	118 x 50	1770 / 401	2360 / 537	2950 / 661	12 / 300	87 / 2212	31 / 799	35 / 900	129 / 3280	28 / 700
XS-PCF-118-70	118 x 70	2478 / 562	3304 / 752	4130 / 925	14 / 350	111 / 2821	35 / 900	35 / 900	153 / 3889	28 / 700
XS-PCF-150-40	150 x 40	1800 / 408	2400 / 546	3000 / 672	12 / 300	78 / 1987	31 / 799	39 / 1000	122 / 3099	30 / 750
XS-PCF-150-50	150 x 50	2250 / 510	3000 / 683	3750 / 840	12 / 300	88 / 2241	31 / 799	39 / 1000	132 / 3353	30 / 750
XS-PCF-150-70	150 x 70	3150 / 714	4200 / 956	5250 / 1176	14 / 350	112 / 2850	35 / 900	39 / 1000	156 / 3963	30 / 750
XS-PCF-180-40	180 x 40	2160 / 490	2880 / 655	3600 / 806	12 / 300	81 / 2065	31 / 799	43 / 1100	126 / 3203	33 / 850
XS-PCF-180-50	180 x 50	2700 / 612	3600 / 819	4500 / 1008	14 / 350	95 / 2420	35 / 900	43 / 1100	140 / 3558	33 / 850
XS-PCF-180-70	180 x 70	3780 / 857	5040 / 1147	6300 / 1411	16 / 400	120 / 3036	40 / 1008	43 / 1100	164 / 4174	33 / 850
XS-PCF-215-40	215 x 40	2580 / 585	3440 / 783	4300 / 963	14 / 350	83 / 2112	35 / 900	47 / 1200	129 / 3275	34 / 875
XS-PCF-215-50	215 x 50	3225 / 731	4300 / 978	5375 / 1204	14 / 350	93 / 2366	35 / 900	47 / 1200	139 / 3529	34 / 875
XS-PCF-215-70	215 x 70	4515 / 1023	6020 / 1370	7525 / 1686	16 / 400	117 / 2982	40 / 1008	47 / 1200	163 / 4145	34 / 875
XS-PCF-260-40	260 x 40	3120 / 707	4160 / 946	5200 / 1165	14 / 350	83 / 2112	35 / 900	51 / 1300	129 / 3286	36 / 925
XS-PCF-260-50	260 x 50	3900 / 884	5200 / 1183	6500 / 1456	16 / 400	97 / 2474	40 / 1008	51 / 1300	144 / 3648	36 / 925
XS-PCF-260-70	260 x 70	5460 / 1238	7280 / 1656	9100 / 2038	18 / 450	121 / 3085	44 / 1111	51 / 1300	168 / 4259	36 / 925
XS-PCF-295-40	295 x 40	3540 / 802	4720 / 1074	5900 / 1322	16 / 400	93 / 2354	40 / 1008	55 / 1400	150 / 3804	43 / 1100
XS-PCF-295-50	295 x 50	4425 / 1003	5900 / 1342	7375 / 1652	16 / 400	103 / 2608	40 / 1008	55 / 1400	160 / 4058	43 / 1100
XS-PCF-295-70	295 x 70	6195 / 1404	8260 / 1879	10325 / 2313	20 / 500	131 / 3319	48 / 1211	55 / 1400	188 / 4769	43 / 1100
XS-PCF-335-40	335 x 40	4020 / 911	5360 / 1219	6700 / 1501	16 / 400	93 / 2364	40 / 1008	59 / 1500	150 / 3800	45 / 1150
XS-PCF-335-50	335 x 50	5025 / 1139	6700 / 1524	8375 / 1876	18 / 450	107 / 2721	44 / 1111	59 / 1500	164 / 4157	45 / 1150
XS-PCF-335-70	335 x 70	7035 / 1595	9380 / 2134	11725 / 2626	20 / 500	131 / 3329	48 / 1211	59 / 1500	188 / 4765	45 / 1150
XS-PCF-410-40	410 x 40	4920 / 1115	6560 / 1492	8200 / 1837	18 / 450	119 / 3024	44 / 1111	63 / 1600	185 / 4696	45 / 1150
XS-PCF-410-50	410 x 50	6150 / 1394	8200 / 1866	10250 / 2296	20 / 500	132 / 3353	48 / 1211	63 / 1600	198 / 5040	45 / 1150
XS-PCF-410-70	410 x 70	8610 / 1952	11480 / 2612	14350 / 3214	24 / 600	160 / 4073	54 / 1363	63 / 1600	229 / 5820	45 / 1150

XSH-STYLE SPECIFICATIONS

TECHNICAL DATA SHEET




MATERIALS

- 1. Shell & cap / Main body: FRP
- 2. Closure cover plate: FRP
- 3. Support legs: Carbon Steel painted
- 4. Inlet flange: FRP
- 5. Outlet flange: FRP
- 6. Air vent: FRP
- 7. Clean drain: FRP
- 8. Deflector plate: FRP

- 9. Tube sheet: PVC / FRP
- 10. Guide plate: PVC / PP
- 11. Closure bolts: SS 316
- 12. Main body gaskets: EPDM
- 13. Main body gaskets: EPDM
- 14. Hoist (lifting arm): SS 316
- 15. Support rod: PA + FRP
- 16. Cartridge element: PP
- 17. Dirty drain: FRP

CHARACTERISTICS

Flow rates: 245 - 3200 m³/h
N° elements: 90 - 410
Elements length: 30/40/50/70
Cartridge flow: Outside - Inside
Housing layout: Horizontal
Features: Side inlet/ bottom outlet
 davit arm available
Optional: Swing bolts
Ideal: High flows and stand alone
Design pressure: 6/10 bar




XSH-STYLE Side Inlet Higher Flow Cartridge Filter Housing

Filter Housing model reference	Cartridges	Flow at 3gpm - 0,68 m ³ /h per 10"	Flow at 4gpm - 0,91 m ³ /h per 10"	Flow at 5gpm - 1,12 m ³ /h per 10"	N1 / N2 (inch / mm)	A (inch / mm)	B (inch / mm)	C (inch / mm)	D (inch / mm)	E (inch / mm)	F (inch / mm)
	Qty. x Length										
XSH-PCF-90-40	90 x 40	1080 / 245	1440 / 328	1800 / 403	10 / 250	52 / 1316	24 / 612	31 / 800	79 / 2019	25 / 640	49 / 1252
XSH-PCF-90-50	90 x 50	1350 / 306	1800 / 410	2250 / 504	10 / 250	52 / 1316	24 / 612	31 / 800	89 / 2273	25 / 640	49 / 1252
XSH-PCF-118-40	118 x 40	1416 / 321	1888 / 430	2360 / 529	10 / 250	46 / 1159	26 / 668	35 / 900	79 / 2013	28 / 700	54 / 1368
XSH-PCF-118-50	118 x 50	1770 / 401	2360 / 537	2950 / 661	12 / 300	56 / 1412	26 / 668	35 / 900	89 / 2267	28 / 700	54 / 1368
XSH-PCF-118-70	118 x 70	2478 / 562	3304 / 752	4130 / 925	14 / 350	76 / 1921	26 / 669	35 / 900	109 / 2775	28 / 700	54 / 1369
XSH-PCF-150-40	150 x 40	1800 / 408	2400 / 546	3000 / 672	12 / 300	47 / 1188	28 / 722	39 / 1000	83 / 2109	30 / 750	58 / 1472
XSH-PCF-150-50	150 x 50	2250 / 510	3000 / 683	3750 / 840	12 / 300	57 / 1442	28 / 722	39 / 1000	93 / 2363	30 / 750	58 / 1472
XSH-PCF-150-70	150 x 70	3150 / 714	4200 / 956	5250 / 1176	14 / 350	77 / 1950	28 / 722	39 / 1000	113 / 2871	30 / 750	58 / 1472
XSH-PCF-180-40	180 x 40	2160 / 490	2880 / 655	3600 / 806	12 / 300	50 / 1266	30 / 772	43 / 1100	87 / 2199	33 / 850	64 / 1622
XSH-PCF-180-50	180 x 50	2700 / 612	3600 / 819	4500 / 1008	14 / 350	60 / 1520	30 / 772	43 / 1100	97 / 2453	33 / 850	64 / 1622
XSH-PCF-180-70	180 x 70	3780 / 857	5040 / 1147	6300 / 1411	16 / 400	80 / 2028	30 / 772	43 / 1100	117 / 2961	33 / 850	64 / 1622
XSH-PCF-215-40	215 x 40	2580 / 585	3440 / 783	4300 / 963	14 / 350	48 / 1212	32 / 821	47 / 1200	86 / 2184	34 / 875	67 / 1696
XSH-PCF-215-50	215 x 50	3225 / 731	4300 / 978	5375 / 1204	14 / 350	58 / 1466	32 / 821	47 / 1200	96 / 2438	34 / 875	67 / 1696
XSH-PCF-215-70	215 x 70	4515 / 1023	6020 / 1370	7525 / 1686	16 / 400	78 / 1974	32 / 821	47 / 1200	116 / 2946	34 / 875	67 / 1696
XSH-PCF-260-40	260 x 40	3120 / 707	4160 / 946	5200 / 1165	14 / 350	48 / 1213	34 / 871	51 / 1300	86 / 2196	36 / 925	71 / 1796
XSH-PCF-260-50	260 x 50	3900 / 884	5200 / 1183	6500 / 1456	16 / 400	58 / 1467	34 / 871	51 / 1300	96 / 2450	36 / 925	71 / 1796
XSH-PCF-260-70	260 x 70	5460 / 1238	7280 / 1656	9100 / 2038	18 / 450	78 / 1975	34 / 871	51 / 1300	116 / 2958	36 / 925	71 / 1796
XSH-PCF-295-40	295 x 40	3540 / 802	4720 / 1074	5900 / 1322	16 / 400	55 / 1406	39 / 984	55 / 1400	97 / 2475	43 / 1100	82 / 2084
XSH-PCF-295-50	295 x 50	4425 / 1003	5900 / 1342	7375 / 1652	16 / 400	65 / 1660	39 / 984	55 / 1400	107 / 2729	43 / 1100	82 / 2084
XSH-PCF-295-70	295 x 70	6195 / 1404	8260 / 1879	10325 / 2313	20 / 500	85 / 2168	39 / 984	55 / 1400	127 / 3237	43 / 1100	82 / 2084
XSH-PCF-335-40	335 x 40	4020 / 911	5360 / 1219	6700 / 1501	16 / 400	53 / 1356	43 / 1084	59 / 1500	98 / 2486	45 / 1150	88 / 2234
XSH-PCF-335-50	335 x 50	5025 / 1139	6700 / 1524	8375 / 1876	18 / 450	63 / 1610	43 / 1084	59 / 1500	108 / 2740	45 / 1150	88 / 2234
XSH-PCF-335-70	335 x 70	7035 / 1595	9380 / 2134	11725 / 2626	20 / 500	83 / 2118	43 / 1084	59 / 1500	128 / 3252	45 / 1150	88 / 2234
XSH-PCF-410-40	410 x 40	4920 / 1115	6560 / 1492	8200 / 1837	18 / 450	75 / 1913	46 / 1176	63 / 1600	128 / 3256	45 / 1150	92 / 2326
XSH-PCF-410-50	410 x 50	6150 / 1394	8200 / 1866	10250 / 2296	20 / 500	85 / 2167	46 / 1176	63 / 1600	138 / 3510	45 / 1150	92 / 2326
XSH-PCF-410-70	410 x 70	8610 / 1952	11480 / 2612	14350 / 3214	24 / 600	105 / 2675	46 / 1176	63 / 1600	158 / 4018	45 / 1150	92 / 2326

XB-STYLE SPECIFICATIONS

TECHNICAL DATA SHEET



MATERIALS

1. Shell & cap / Main body: FRP
2. Closure cover plate: FRP
3. Support legs: FRP
4. Inlet flange: FRP
5. Outlet flange: FRP
6. Air vent: FRP
7. Drain: FRP
8. Deflector plate: FRP
9. Tube sheet: PVC / FRP
10. Guide plate: PVC / PP
11. Lifting lugs: FRP
12. Closure bolts: SS 316
13. Main body gaskets: EPDM
15. Support rod: PA + FRP
16. Cartridge element: PP
22. Internal support rod: FRP + PA

CHARACTERISTICS

Flow rates: 275 - 3200 m³/h
N° elements: 101 - 410
Elements length: 30/40/50/70
Cartridge flow: Outside - Inside
Housing layout: Vertical
Features: Bottom Inlet / Top Outlet
 davit arm available
 cartridge removal as package
Optional: Swing bolts
Ideal: High flows and stand alone
Design pressure: 6/10 bar




XB-STYLE

Bottom Inlet type Higher Flow Cartridge Filter Housing


Filter Housing model reference	Cartridges	Flow at 3gpm - 0,68 m³/h per 10"	Flow at 4gpm - 0,91 m³/h per 10"	Flow at 5gpm - 1,12 m³/h per 10"	N1 / N2 (inch / mm)	A (inch / mm)	C (inch / mm)	D (inch / mm)
	Qty. x Length							
XB-PCF-101-40	101 x 40	1212 / 275	1616 / 368	2020 / 452	10 / 250	27 / 685	31 / 800	112 / 2857
XB-PCF-101-50	101 x 50	1515 / 343	2020 / 460	2525 / 566	10 / 250	27 / 685	31 / 800	122 / 3111
XB-PCF-125-40	125 x 40	1500 / 340	2000 / 455	2500 / 560	10 / 250	27 / 685	35 / 900	117 / 2964
XB-PCF-125-50	125 x 50	1875 / 425	2500 / 569	3125 / 700	10 / 250	27 / 685	35 / 900	127 / 3218
XB-PCF-125-70	125 x 70	2625 / 595	3500 / 796	4375 / 980	12 / 300	35 / 900	35 / 900	151 / 3841
XB-PCF-160-40	160 x 40	1920 / 435	2560 / 582	3200 / 717	12 / 300	31 / 799	39 / 1000	125 / 3178
XB-PCF-160-50	160 x 50	2400 / 544	3200 / 728	4000 / 896	12 / 300	31 / 799	39 / 1000	135 / 3432
XB-PCF-160-70	160 x 70	3360 / 762	4480 / 1019	5600 / 1254	14 / 350	35 / 900	39 / 1000	159 / 4041
XB-PCF-195-40	195 x 40	2340 / 530	3120 / 710	3900 / 874	12 / 300	31 / 799	43 / 1100	131 / 3331
XB-PCF-195-50	195 x 50	2925 / 663	3900 / 887	4875 / 1092	14 / 350	35 / 900	43 / 1100	145 / 3686
XB-PCF-195-70	195 x 70	4095 / 928	5460 / 1242	6825 / 1529	16 / 400	40 / 1008	43 / 1100	169 / 4302
XB-PCF-240-40	240 x 40	2880 / 653	3840 / 874	4800 / 1075	14 / 350	35 / 900	47 / 1200	134 / 3397
XB-PCF-240-50	240 x 50	3600 / 816	4800 / 1092	6000 / 1344	16 / 400	40 / 1008	47 / 1200	148 / 3759
XB-PCF-240-70	240 x 70	5040 / 1142	6720 / 1529	8400 / 1882	18 / 450	44 / 1111	47 / 1200	172 / 4370
XB-PCF-280-40	280 x 40	3360 / 762	4480 / 1019	5600 / 1254	14 / 350	35 / 900	51 / 1300	134 / 3414
XB-PCF-280-50	280 x 50	4200 / 952	5600 / 1274	7000 / 1568	16 / 400	40 / 1008	51 / 1300	149 / 3776
XB-PCF-280-70	280 x 70	5880 / 1333	7840 / 1784	9800 / 2195	20 / 500	48 / 1211	51 / 1300	177 / 4487
XB-PCF-315-40	315 x 40	3780 / 857	5040 / 1147	6300 / 1411	16 / 450	40 / 1008	55 / 1400	154 / 3920
XB-PCF-315-50	315 x 50	4725 / 1071	6300 / 1433	7875 / 1764	18 / 450	44 / 1111	55 / 1400	163 / 4139
XB-PCF-315-70	315 x 70	6615 / 1499	8820 / 2007	11025 / 2470	20 / 500	48 / 1211	55 / 1400	187 / 4747
XB-PCF-370-40	370 x 40	4440 / 1006	5920 / 1347	7400 / 1658	16 / 400	40 / 1008	59 / 1500	155 / 3931
XB-PCF-370-50	370 x 50	5550 / 1258	7400 / 1684	9250 / 2072	18 / 450	44 / 1111	59 / 1500	169 / 4288
XB-PCF-370-70	370 x 70	7770 / 1761	10360 / 2357	12950 / 2901	24 / 600	54 / 1363	59 / 1500	199 / 5048
XB-PCF-410-40	410 x 40	4920 / 1115	6560 / 1492	8200 / 1837	18 / 450	44 / 1111	63 / 1600	176 / 4481
XB-PCF-410-50	410 x 50	6150 / 1394	8200 / 1866	10250 / 2296	20 / 500	48 / 1211	63 / 1600	190 / 4834
XB-PCF-410-70	410 x 70	8610 / 1952	11480 / 2612	14350 / 3214	24 / 600	54 / 1363	63 / 1600	224 / 5694

HV-Q-X-STYLE SPECIFICATIONS

TECHNICAL DATA SHEET



HV-X




HV-Q

MATERIALS

1. Shell & cap / Main body: FRP
2. Closure cover plate: FRP
3. Support legs: FRP / SS316
4. Inlet flange: FRP
5. Outlet flange: FRP
6. Air vent: FRP / PP
7. Clean drain: FRP / PP
9. Tube sheet: PVC / FRP
11. Lifting lugs: FRP
12. Closure bolts: SS 316
13. Main body gaskets: EPDM
14. Hoist (lifting arm): SS 316
18. O-ring support plate: PVC
19. Structural plate: FRP
20. Securing plate: PP
21. Locking rings: PP
23. High Flow cartridge: PP
24. Baskets: PP

CHARACTERISTICS

Flow rates: 40 - 2700 m³/h
N° elements: 1 - 45
Elements length: 40" & 60"
Cartridge flow: Inside - Outside
Housing layout: Vertical
Features: Side Inlet / Bottom Outlet
 davit arm available
 cartridge removal as
 package available
Optional: Swing bolts
Ideal: High flows and stand alone
Design pressure: 6/10 bar





HV-Q-X-STYLE

Quick Opening High Flow Filter Housing


Filter Housing model reference	Cartridges	Design Flow gpm / m ³ /h	N1 / N2 (inch / mm)	A (inch / mm)	B (inch / mm)	C (inch / mm)	D (inch / mm)	E (inch / mm)
	Qty. x Length							
HV-Q-PCF-1-40	1 x 40	176 / 40	3 / 80	49 / 1236	4 / 104	8 / 200	52 / 1328	7 / 180
HV-Q-PCF-1-60	1 x 60	264 / 60	4 / 100	68 / 1734	4 / 114	8 / 200	72 / 1836	7 / 180
HV-Q-PCF-2-40	2 x 40	352 / 80	4 / 100	61 / 1561	32 / 810	16 / 400	71 / 1813	12 / 310
HV-Q-PCF-2-60	2 x 60	528 / 120	6 / 150	81 / 2069	52 / 1318	16 / 400	91 / 2321	12 / 310
HV-Q-PCF-3-40	3 x 40	528 / 120	6 / 150	61 / 1559	31 / 779	20 / 500	71 / 1813	14 / 360
HV-Q-PCF-3-60	3 x 60	792 / 180	6 / 150	81 / 2067	51 / 1287	20 / 500	91 / 2321	14 / 360
HV-Q-PCF-7-40	7 x 40	1233 / 280	8 / 200	66 / 1684	48 / 1215	24 / 600	86 / 2187	16 / 410
HV-Q-PCF-7-60	7 x 60	1849 / 420	10 / 250	86 / 2192	68 / 1723	24 / 600	96 / 2441	16 / 410
HV-X-PCF-10-40	10 x 40	1761 / 400	10 / 250	100 / 2541	27 / 685	31 / 800	128 / 3241	25 / 640
HV-X-PCF-10-60	10 x 60	2641 / 600	12 / 300	126 / 3213	31 / 799	31 / 800	154 / 3913	25 / 640
HV-X-PCF-12-40	12 x 40	2113 / 480	10 / 250	104 / 2630	27 / 685	35 / 900	132 / 3361	28 / 700
HV-X-PCF-12-60	12 x 60	3169 / 720	12 / 300	130 / 3302	31 / 799	35 / 900	159 / 4033	28 / 700
HV-X-PCF-19-40	19 x 40	3346 / 760	12 / 300	103 / 2609	31 / 799	39 / 1000	135 / 3437	30 / 750
HV-X-PCF-19-60	19 x 60	5018 / 1140	20 / 400	143 / 3629	48 / 1211	39 / 1000	175 / 4457	30 / 750
HV-X-PCF-27-40	27 x 40	4754 / 1080	16 / 400	116 / 2948	40 / 1008	47 / 1200	151 / 3846	34 / 875
HV-X-PCF-27-60	27 x 60	7131 / 1620	18 / 450	142 / 3609	44 / 1111	47 / 1200	177 / 4507	34 / 875
HV-X-PCF-29-40	29 x 40	5106 / 1160	16 / 400	121 / 3085	40 / 1008	51 / 1300	157 / 3994	36 / 925
HV-X-PCF-29-60	29 x 60	7659 / 1740	20 / 500	149 / 3796	48 / 1211	51 / 1300	183 / 4655	36 / 925
HV-X-PCF-37-40	37 x 40	6515 / 1480	18 / 450	133 / 3378	44 / 1111	55 / 1400	179 / 4557	43 / 1100
HV-X-PCF-37-60	37 x 60	9772 / 2220	24 / 600	169 / 4288	54 / 1363	55 / 1400	215 / 5467	43 / 1100
HV-X-PCF-39-40	39 x 40	6867 / 1560	18 / 450	133 / 3374	44 / 1111	59 / 1500	179 / 4553	45 / 1150
HV-X-PCF-39-60	39 x 60	10301 / 2340	24 / 600	173 / 4383	54 / 1363	59 / 1500	219 / 5562	45 / 1150
HV-X-PCF-45-40	45 x 40	7924 / 1800	20 / 500	150 / 3804	48 / 1211	63 / 1600	216 / 5476	47 / 1200
HV-X-PCF-45-60	45 x 60	11885 / 2700	24 / 600	180 / 4564	54 / 1363	63 / 1600	246 / 6236	47 / 1200

HH-Q-X-STYLE SPECIFICATIONS

TECHNICAL DATA SHEET



HH-Q



HH-X

MATERIALS

1. Shell & cap / Main body: FRP
2. Closure cover plate: FRP
3. Support legs: Carbon Steel painted
4. Inlet flange: FRP
5. Outlet flange: FRP / PP
6. Air vent: FRP / PP
7. Clean drain: FRP / PP
9. Tube sheet: PVC / FRP
12. Closure bolts: SS 316
13. Main body gaskets: EPDM
14. Hoist (lifting arm): SS 316
18. O-ring support plate: PVC
19. Structural plate: FRP
20. Securing plate: PP
21. Locking rings: PP
23. High Flow cartridge: PP
24. Baskets: PA + FRP

CHARACTERISTICS

Flow rates: 40 - 2700 m³/h

N° elements: 1 - 45

Elements length: 40" & 60"

Cartridge flow: Inside - Outside


Housing layout: Horizontal

Features: Side Inlet / Bottom Outlet
davit arm available

Optional: Swing bolts

Ideal: High flows and stand alone

Design pressure: 6/10 bar




HH-Q-X-STYLE

Quick Opening High Flow Filter Housing


Filter Housing model reference	Cartridges	Design Flow gpm / m ³ /h	N1 / N2 (inch / mm)	A (inch / mm)	B (inch / mm)	C (inch / mm)	D (inch / mm)	E (inch / mm)	F (inch / mm)
	Qty. x Length								
HH-Q-PCF-1-40	1 x 40	176 / 40	3 / 80	49 / 1236	4 / 104	8 / 200	52 / 1328	7 / 180	9 / 218
HH-Q-PCF-1-60	1 x 60	264 / 60	4 / 100	68 / 1734	4 / 104	8 / 200	72 / 1836	7 / 180	9 / 218
HH-Q-PCF-2-40	2 x 40	352 / 80	4 / 100	61 / 1561	52 / 1318	16 / 400	71 / 1813	12 / 310	13 / 318
HH-Q-PCF-2-60	2 x 60	528 / 120	6 / 150	81 / 2069	52 / 1318	16 / 400	91 / 2321	12 / 310	13 / 318
HH-Q-PCF-3-40	3 x 40	528 / 120	6 / 150	61 / 1559	51 / 1287	20 / 500	71 / 1813	14 / 360	14 / 368
HH-Q-PCF-3-60	3 x 60	792 / 180	6 / 150	81 / 2067	51 / 1287	20 / 500	91 / 2321	14 / 360	14 / 368
HH-Q-PCF-7-40	7 x 40	1233 / 280	8 / 200	66 / 1684	53 / 1356	24 / 600	86 / 2187	16 / 410	16 / 418
HH-Q-PCF-7-60	7 x 60	1849 / 420	10 / 250	86 / 2192	53 / 1356	24 / 600	96 / 2441	16 / 410	16 / 418
HH-X-PCF-10-40	10 x 40	1761 / 400	10 / 250	100 / 2541	24 / 600	31 / 800	128 / 3241	25 / 640	49 / 1240
HH-X-PCF-10-60	10 x 60	2641 / 600	12 / 300	126 / 3213	24 / 600	31 / 800	154 / 3913	25 / 640	49 / 1240
HH-X-PCF-12-40	12 x 40	2113 / 480	10 / 250	104 / 2630	26 / 650	35 / 900	132 / 3361	28 / 700	53 / 1350
HH-X-PCF-12-60	12 x 60	3169 / 720	12 / 300	130 / 3302	26 / 650	35 / 900	159 / 4033	28 / 700	53 / 1350
HH-X-PCF-19-40	19 x 40	3346 / 760	12 / 300	103 / 2609	28 / 700	39 / 1000	135 / 3437	30 / 750	57 / 1450
HH-X-PCF-19-60	19 x 60	5018 / 1140	20 / 400	143 / 3629	28 / 700	39 / 1000	175 / 4457	30 / 750	57 / 1450
HH-X-PCF-27-40	27 x 40	4754 / 1080	16 / 400	116 / 2948	31 / 800	47 / 1200	151 / 3846	34 / 875	66 / 1675
HH-X-PCF-27-60	27 x 60	7131 / 1620	18 / 450	142 / 3609	31 / 800	47 / 1200	177 / 4507	34 / 875	66 / 1675
HH-X-PCF-29-40	29 x 40	5106 / 1160	16 / 400	121 / 3085	33 / 850	51 / 1300	157 / 3994	36 / 925	70 / 1775
HH-X-PCF-29-60	29 x 60	7659 / 1740	20 / 500	149 / 3796	33 / 850	51 / 1300	183 / 4655	36 / 925	70 / 1775
HH-X-PCF-37-40	37 x 40	6515 / 1480	18 / 450	133 / 3378	35 / 900	55 / 1400	179 / 4557	43 / 1100	79 / 2000
HH-X-PCF-37-60	37 x 60	9772 / 2220	24 / 600	169 / 4288	35 / 900	55 / 1400	215 / 5467	43 / 1100	79 / 2000
HH-X-PCF-39-40	39 x 40	6867 / 1560	18 / 450	133 / 3374	37 / 950	59 / 1500	179 / 4553	45 / 1150	83 / 2100
HH-X-PCF-39-60	39 x 60	10301 / 2340	24 / 600	173 / 4383	37 / 950	59 / 1500	219 / 5562	45 / 1150	83 / 2100
HH-X-PCF-45-40	45 x 40	7924 / 1800	20 / 500	150 / 3804	39 / 1000	63 / 1600	216 / 5476	47 / 1200	87 / 2200
HH-X-PCF-45-60	45 x 60	11885 / 2700	24 / 600	180 / 4564	39 / 1000	63 / 1600	246 / 6236	47 / 1200	87 / 2200

B-Q-X-STYLE SPECIFICATIONS

TECHNICAL DATA SHEET



B-X




B-Q

MATERIALS

1. Shell & cap / Main body: FRP
3. Support legs: FRP / SS316
4. Inlet flange: FRP
5. Outlet flange: FRP
6. Air Vent: FRP / PP
7. Clean drain: FRP / PP
9. Tube sheet: PVC / FRP
11. Lifting lugs: FRP
13. Main body gaskets: EPDM
18. O'ring support plate: PVC
19. Structural plate: FRP
20. Securing plate: PP
21. Locking rings: PP
24. Baskets: PP
25. Bag filters: PP

CHARACTERISTICS

Flow rates: 21 - 600 m³/h
N° elements: 1 - 45
Elements length: 17" & 32"
Cartridge flow: Inside - Outside
Housing layout: Vertical
Features: Side inlet / Bottom Outlet
 davit arm available
 bags removal as package available
Optional: Swing bolts
Ideal: High flows and stand alone
Design pressure: 6/10 bar




B-Q-X-STYLE

Quick Opening High Flow Filter Housing

Filter Housing model reference	Cartridges	Maximum Flow gpm / m ³ /h	N1 / N2 (inch / mm)	A (inch / mm)	B (inch / mm)	C (inch / mm)	D (inch / mm)	E (inch / mm)
	Qty. x Length							
B-Q-PCF-1-17	1 x 17	90 / 21	3 / 80	28 / 719	4 / 104	8 / 200	32 / 811	7 / 180
B-Q-PCF-1-32	1 x 32	176 / 40	4 / 100	40 / 1023	4 / 114	8 / 200	44 / 1125	7 / 180
B-Q-PCF-2-17	2 x 17	180 / 41	4 / 100	41 / 1044	4 / 104	16 / 400	51 / 1296	12 / 310
B-Q-PCF-2-32	2 x 32	352 / 80	6 / 150	53 / 1358	24 / 607	16 / 400	63 / 1610	12 / 310
B-Q-PCF-3-17	3 x 17	271 / 62	6 / 150	41 / 1042	10 / 262	20 / 500	51 / 1296	14 / 360
B-Q-PCF-3-32	3 x 32	528 / 120	6 / 150	53 / 1356	23 / 576	20 / 500	63 / 1610	14 / 360
B-Q-PCF-7-17	7 x 17	632 / 144	8 / 200	46 / 1167	27 / 698	24 / 600	56 / 1416	16 / 410
B-Q-PCF-7-32	7 x 32	1233 / 280	10 / 250	58 / 1481	40 / 1012	24 / 600	68 / 1730	16 / 410
B-X-PCF-10-17	10 x 17	902 / 205	10 / 250	80 / 2024	27 / 685	31 / 800	107 / 2724	25 / 640
B-X-PCF-10-32	10 x 32	1761 / 400	12 / 300	99 / 2502	31 / 799	31 / 800	126 / 3202	25 / 640
B-X-PCF-12-17	12 x 17	1083 / 246	10 / 250	83 / 2113	27 / 685	35 / 900	112 / 2844	28 / 700
B-X-PCF-12-32	12 x 32	2113 / 480	12 / 300	102 / 2591	31 / 799	35 / 900	131 / 3322	28 / 700
B-X-PCF-19-17	19 x 17	1715 / 390	12 / 300	82 / 2092	31 / 799	39 / 1000	115 / 2920	30 / 750
B-X-PCF-19-32	19 x 32	3346 / 760	20 / 400	115 / 2918	48 / 1211	39 / 1000	147 / 3746	30 / 750
B-X-PCF-27-17	27 x 17	2437 / 554	16 / 400	96 / 2431	40 / 1008	47 / 1200	131 / 3329	34 / 875
B-X-PCF-27-32	27 x 32	4754 / 1080	18 / 450	114 / 2898	44 / 1111	47 / 1200	149 / 3796	34 / 875
B-X-PCF-29-17	29 x 17	2617 / 595	16 / 400	101 / 2568	40 / 1008	51 / 1300	137 / 3477	36 / 925
B-X-PCF-29-32	29 x 32	5106 / 1160	20 / 500	121 / 3085	48 / 1211	51 / 1300	155 / 3944	36 / 925
B-X-PCF-37-17	37 x 17	3339 / 759	18 / 450	113 / 2861	44 / 1111	55 / 1400	159 / 4040	43 / 1100
B-X-PCF-37-32	37 x 32	6515 / 1480	24 / 600	141 / 3577	54 / 1363	55 / 1400	187 / 4756	43 / 1100
B-X-PCF-39-17	39 x 17	3519 / 800	18 / 450	112 / 2857	44 / 1111	59 / 1500	159 / 4036	45 / 1150
B-X-PCF-39-32	39 x 32	6867 / 1560	24 / 600	145 / 3672	54 / 1363	59 / 1500	191 / 4851	45 / 1150
B-X-PCF-45-17	45 x 17	4061 / 923	20 / 500	129 / 3287	48 / 1211	63 / 1600	195 / 4959	47 / 1200
B-X-PCF-45-32	45 x 32	7924 / 1800	24 / 600	152 / 3853	54 / 1363	63 / 1600	218 / 5525	47 / 1200

S-Q-X-STYLE SPECIFICATIONS

TECHNICAL DATA SHEET



S-Q

MATERIALS


1. Shell & cap / Main body: FRP
2. Closure cover plate: FRP
3. Support legs: FRP / SS316
4. Inlet flange: FRP
5. Outlet flange: FRP
6. Air vent: FRP / PP
7. Clean drain: FRP / PP
9. Tube sheet: PVC / FRP
11. Lifting lugs: FRP
12. Closure bolts: SS 316
13. Main body gaskets: EPDM
16. Basket Filter Element: PVC / SS316 /
Superduplex

PIEDMONT BASKET STRAINERS

FRP Piedmont Basket Type Strainers are perfect solutions for preventing relatively bigger particles to pass into the main pipe line in order to protect the expensive and fragile equipment such as pumps, flow meters, nozzles and valves which could stop functioning in case of solid particle accumulation. Primary areas of application, but not limited to, could be Heating and Cooling Systems, Side Stream Filtration Systems, Sewage Lines...

- Housing made in FRP (fiber glass reinforced polyester)
- Baskets made in Suerduplex for high corrosion resistance
- EN13121 or ASME X design
- Flow rates from 100 gpm to 15000 gpm
- Pipe sizes from 2" to 24"
- Standard design pressure 150 psi. Higher pressures are available
- Available with wedge wire and mesh liners.
- Swing bolt closure for quick opening available under request
- Davit arm for larger vessels to facilitate the removal of the basket


www.piedmontpacific.com



S-X

FILTER CARTRIDGE SPECIFICATIONS

TECHNICAL DATA SHEET



Piedmont High Flow Pleated Filter Cartridges are especially designed for high flow filtration applications and will replace Pall Ultiplex brand. Unique rigid hard cage as outer case enables the High Flow filters to undertake large differential pressures during the filtration process.

Larger diameter with less filter elements, but more filtration surface area leads to higher flow rate and longer service life. Both CAPEX and OPEX can be reduced.

Suitable for various applications like RO-pretreatment, condensate filtration, seawater, desalination and (petro)chemical and pharmaceutical applications.

Features

- Deep pleated structure with multiple filtration media
- High dirt holding capacity
- Ultimate retention efficiency
- Inside-out flow to hold most debris in

Cartridge Dimensions

Removing Ratings (Absolute)	1, 3, 5, 10, 20, 40 µm and others available
Surface of filtration	7.98 m ² / 85.90 ft ²
Outside Diameter	6 inches / 152 mm
Length	40 inches / 1 016 mm, 60 inches / 1 524 mm

Material of construction

Filter Media	Depth Type Multimedia Polypropylene
Core Material	Polypropylene
End Cap Material	Rigid Hard Cage
Support Layer Material	Polypropylene
Gasket / O-ring Material	EPDM / VITON

Operating Conditions

Maximum Operating Temperature	180 °F / 82°C
Maximum Flow Rate	40" : 343gpm / 78 m ³ / hr 60" : 500gpm / 113m ³ / hr
Recommended Change-Out Differential Pressure	30psid @68 °F (2.1bar @ 20 °C)

Piedmont High Flow Cartridge Ordering Guide

Cartridge Design	Cartridge Length	Material (Media / Plastic Components)	Removal Rating (Nominal Micron)	O-ring Material
Max Pleated PL Series	40 – 40 " (1,016 mm) 60 – 60 " (1,524 mm)	PP – Polypropylene Micron Fiber Media	P010– 1 µm P030– 3 µm P050– 5 µm P100– 10 µm P200– 20 µm P400– 40 µm	E=EPDM V=Fluororubber S=Silicon N=Buna-N rubber

Features / Benefits

High flow capacity up to 500 gpm per cartridge

- Reduced Filter Usage - minimizes product loss, labor cost, disposal costs, operator exposure and downtime for filter change-out.

Absolute rating

- Reproducible effluent quality throughout the filter's life.

Pleated design

- Larger usable filtration surface area, higher dirty holding capacity longer life time.


Supporting core design

- Strengthen filter cartridge, easy to change.

Easy to use

- No special tools or hardware required for filter change-out - minimizes downtime
- Handle design - facilitates easy cartridge installation and removal

Typical Cartridge Flow Rates



TESTIMONIALS

"Piedmont provided outstanding technical support to our project. Their engineering team is not only an expert of the Piedmont products but they have experienced knowledge of the overall desalination process and piping design. I would recommend them for any large desalination plant."

- Damjoo R., Senior Project Manager, Korean EPC company



"The product quality of Piedmont Cartridge Filter Housings and Flexible Couplings helps us keep high reputation towards our customers. Piedmont's support during the design, execution and operation phases is outstanding; it reduces the project risks regarding these components."

- Diego P., Owner, Water treatment OEM

"Our company is using Piedmont for our large desalination projects. They are flexible commercially and competitive. We wouldn't hesitate to use them again"

- Team Leader Purchasing Dept., Desalination EPC company




PIEDMONT'S REFERENCE LIST



Project	Contractor	Capacity (m ³ /day)
Sorek, Israel	Via Maris Desalination	624 000
Fujairah, UAE	Acciona	455 000
Umm Al Houl, Qatar	Acciona	284 000
Barka, Oman	Suez	281 000
Orange County, CA, USA	H2O Innovation	265 000
Sydney, Australia	Veolia	250 000
Mirfa, Abu Dhabi, UAE	Suez	240 000
Torre Vieja, Spain	Acciona	240 000
Escondida, Chile	Doosan	220 000
Sant Joan Despí, Spain	Cadagua	206 000
Carlsbad, CA, USA	IDE Technologies	204 000
Basra, Iraq	Sidem/Veolia	200 000
Qurayyat, Oman	Hyflux	200 000
Tianjin SDIC, China	IDE Technologies	200 000
Barcelona, Spain	Suez	200 000
Al Ghubrah, Oman	International Water Treatment LLC	191 000
Aguilas-Guadalupe, Spain	Cadagua - Sacyr	180 000
Reliance, India	IDE Technologies	168 000
Ras Abu Fontas, Qatar	Acciona	164 000
Sadara, Saudi Arabia	Sidem/Veolia	150 000
SSDP 2, Perth, Australia	Tecnicas Reunidas Valoriza	140 000
SSDP 1, Perth, Australia	Tecnicas Reunidas Valoriza	140 000
Valdelentisco, Spain	Cadagua	140 000
Busan, South Korea	VWS Westgarth	127 000
Gold Coast, Australia	Veolia	125 000
Dubai Seawater, Dubai, UAE	Xylem (ITT)	113 000
Tampa, FL, USA	American Water Acciona	95 000
Sharjah, UAE	Aqua Engineering GmbH	91 000
Antofagasta, Chile	Aguas Antofagasta	85 000
Las Palmas, Canary Islands	Various clients	75 000
Luggage Point, Brisbane, Australia	Doosan	70 000
Escombreras, Cartagena, Spain	Tedagua	68 000
Alicante, Spain	Inima	65 000
Cartagena, Spain	Acciona	65 000
San Pedro del Pinatar, Spain	Suez	65 000
Palm Jumeirah, Dubai, UAE	ACWA Emirates LLC	64 400
Rambla Morales, Spain	Tecnicas Reunidas	60 000
Jeddah, Saudi Arabia	Kalsep	57 700
Namwater (Uramin), Namibia, Africa	Keyplan (Pty) Ltd.	55 000
Antofagasta, Chile	Inima	52 000
Yanbu, Saudi Arabia	Cadagua	50 000
Barka, Oman, UAE	Osmoflo	47 000
Candelaria Minera, Chile	Aqualia	45 000
Curacao, Lesser Antilles	Suez	45 000
Jeddah, Saudi Arabia, UAE	Wier Westgarth	34 000
Santa Barbara, CA, USA	IDE Technologies	33 000
Moncofa, Spain	GS Inima	30 000
Lancaster, PA, USA	Harn RO	30 000
Jeddah, Saudi Arabia, UAE	SETE Energy Saudia	30 000
Brownsville, TX, USA	SRWA	28 000
Los Cabos, Mexico	Inima	17 000
West Hub, Luanda, Angola	VWS Westgarth	16 000
Five Forks WTP, USA	Aquious Advanced	14 500
Alcudia, Majorca	Sadyt	14 000
Andraxt, Majorca	Suez	14 000
Tenerife, Barcelona, Spain	Aqualia	10 000
Serayah, Singapore	Graham-Tek	10 000
Menorca, Ciutadella, Minorca	Acciona	10 000
Plutonio, Luanda, Angola	VWS Westgarth	10 000




Fujairah, UAE



Orange County, CA



Mirfa, Abu Dhabi



Escondida, Chile



Carlsbad, CA



Perth, Australia

AMERICAS | EUROPE | MIDDLE EAST & AFRICA | ASIA-PACIFIC



WORLDWIDE PRESENCE

Piedmont

1048 La Mirada Court,
Vista, CA 92081, USA

Barroeta Aldamar, 6 - planta 4
Bilbao-Bizkaia 48001, SPAIN

1 760.305.7616 | orders@piedmontpacific.com

www.piedmontpacific.com

FRP BAG FILTERS • FRP STRAINERS • CARTRIDGE ELEMENTS •
GROOVED END FLEXIBLE COUPLINGS • END CAPS • FIBERMOVE